



BUNCHED Copper Conductor
FR-LSH base INSULATION
FR-LSH skin INSULATION

FR-LSH SINGLE CORE FLEXIBLE CABLE

Document ID:A13:I44O21A13:I42A13:I46A13:I45

Particulars	1 CORE X 25 Sq .mm
Name of MANUFACTURER	AMPSCAB INDIA PVT LTD
Type of cable	Fr-LSH
Voltage Grade (Volts)	1100
No of cores x size in sq.mm	1 CORE X 25 SQ.mm
Conductor	
material	plainannealed high conductivity FLEXIBEL copper conductor as per class 5 of
b) Max. d.c. resistance of conductor at 20 C ohm/km)	0.78
c)shape of conductor	flexibel Circular
Insulation	
a) material	FR-LSH PVC TYPE D as per IS 5831/1984 latest
b) Nomonal thickness (mm)	1.2
c) core identification	red/black/blue/yellow/white/grey
Approx overall diameter of the cable in mm	8.8
Maximum conductor temperature under noramal operating condition	70 C
Maximum conductor temperature at the terminal of circuit	160 C
high voltage test	3kv
Coninuous Current carrying capacities	
a) in Air at 40 C (A)	111
Applicable Standard	IS 8130/2013 IS 694/2010.ect with
Minimum bending radius	6 times Overall diameter
FR-LSH Properties	
a) Oxgen index	MIN 29 % as per ASTM D- 2863
b) Temperature index	MIN 250 Deg C as per ASTM D-2843
c) Smoke density ratting	MAX 60% AS PER ASTM D- 2843
d) Acid gas generation	MAX 20% AS PER IEC 60754-1
standard packing length	100 Meter coil 300 meter coil 500 1000 m (Higher quantity in Wooden drum)

Rev . No: 00

issued Date 10/06/2024
